



702 Signature

Technical features Decoupled Carbon Dome™ tweeter

Solid Body Tweeter on top Continuum[™] cone FST[™] midrange Decoupled midrange Aerofoil[™] Profile bass cones

Flowport*

Description 3-way vented-box system

Drive Units 1x ø25mm (1 in) Decoupled Carbon Dome high-frequency

1x ø150mm (6 in) Continuum cone FST midrange

3x ø165mm (6.5 in) Aerofoil Profile bass

Frequency range (-6dB) -6dB at 28Hz and 33kHz

 Frequency response
 45Hz - 28kHz ±3dB

 Sensitivity
 90dB spl (2.83V_{RMS}, 1m)

Harmonic distortion 2nd and 3rd harmonics (90dB, 1m)

<1% 86Hz - 28k

<0.5% 110Hz - 20kHz Nominal impedance 8Ω (minimum 3.1Ω)

Recommended amplifier 30W - 300W into 8Ω on unclipped programme

power

Dimensions Height: 994mm (39 in) cabinet only

1087mm (42.8 in) including tweeter and plinth 200mm (7.9 in) cabinet only

Width: 366mm (14.4 in) including plinth

337mm (13.3 in) cabinet only

364mm (14.3 in) including grille and terminals

Depth: 414mm (16.3 in) including plinth

Weight 29.5kg (65 lb

Finishes Cabinet Datuk Gloss

Grille: Black

705 Signature

Technical features Decoupled Carbon Dome tweeter

Solid Body Tweeter on top Continuum cone bass/midrange

Flowport

Description 2-way vented-box system

Drive Units 1x ø25mm (1 in) Decoupled Carbon Dome high-frequency

1x Ø165mm (6.5 in) Continuum cone bass / midrange

Frequency range (-6dB) -6dB at 45Hz and 33kHz
Frequency response 50Hz - 28kHz ±3dB

 Frequency response
 50Hz - 28kHz ±3dB

 Sensitivity
 88dB spl (2.83V_{RMS}, 1 m)

Harmonic distortion 2nd and 3rd harmonics (90dB, 1m)

<1% 100Hz - 22kHz <0.5% 150Hz -

Nominal impedance 8Ω (minimum 3.7Ω)

Recommended amplifier 30W - 120W into 8Ω on unclipped programme

power

Dimensions Height: 340mm (13.4 in) cabinet only 407mm (16 in) including tweeter

200mm (7.8 in)

200mm (7.8 ir

Width: 285mm (11.2 in) cabinet only

Depth: 301mm (11.9 in) including grille and terminals

Weight 9.3kg (20.5 lb)

Finishes Cabinet Datuk Gloss

Grille: Black

