



## See nothing, hear everything

The CWM663 features a blue Kevlar® bass/midrange driver housed in a die-cast chassis which provides the extra rigidity to provide a cleaner, faster bass. Its aluminium tweeter also incorporates a Nautilus™ tube to absorb unwanted sonic radiation. The CWM663 also utilises a three-position high frequency switch to fine tune the sound. The speaker is incredibly easy to install incorporating QuickDogs™ and plug-and-play functionality.

## Technical Specifications

<b>Description</b>	2-way in-wall system
<b>Drive units</b>	1x ø25mm (1in) Nautilus™ tube loaded aluminium dome tweeter 1x ø150mm (6in) blue Kevlar® cone bass/midrange
<b>Frequency Range (-6dB)</b>	45Hz – 50kHz
<b>Maximum Amp Power</b>	25 – 150w
<b>Sensitivity SPL (2.83V, 1m)</b>	88dB
<b>Impedance Nominal (min)</b>	8Ω (4.5Ω)
<b>Frame height</b>	315mm (12.4in)
<b>Frame width</b>	221mm (8.7in)
<b>Cut-out height</b>	279mm (11in)
<b>Cut-out width</b>	183mm (7.2in)
<b>Depth behind surface</b>	95mm (3.7in)
<b>Protrusion</b>	4mm (0.2in)
<b>Pre-mount Kit</b>	PMK W6
<b>Back Box</b>	BB 6W